Incubators - dry baths

AccuBlock™ Digital Dry Baths

Labnet's single and dual block *AccuBlock* Digital Dry Baths provide users with digital performance and convenience at an analog price.

Useful for a variety of applications in molecular biology, histology, clinical, environmental and industrial settings, the dry baths feature a broad temperature range, up to 150°C, and excellent uniformity. A microprocessor regulates the high wattage heater to provide precise, accurate control and rapid heating. The stainless steel block chamber ensures an even transfer of heat from the heating element to the block. Temperature is easily set using arrow keys while the value is shown on the large display. The user calibration function allows for easy calibration to in-house standards when required.

The dry bath is available as a single or dual block model. Interchangeable blocks (sold separately on page 26) are available to accommodate a wide variety of tubes, plates and slides. Solid blocks are also available for custom machining.

Each dry bath is supplied with a block lifter that enables the user to exchange blocks easily, even when the block is hot.



- Precise microprocessor control
- Broad temperature range, to 150°C
- Large digital display
- **■** Easy user calibration
- Single and dual block models

SPECIFICATIONS

Temperature range Ambient +5° to 150°C, in 0.1° increments

Temperature resolution 0.1°C Temperature uniformity $\pm 0.2^{\circ}\text{C}$ Temperature accuracy $\pm 0.3^{\circ}\text{C}$

Temperature control Microprocessor Block chamber construction Stainless steel

Dimensions (W x D x H) 7.9 x 10.4 x 3.3 in/20 x 26.5 x 8.3 cm

Weight 4.8 lb/2.2 kg

Electrical 230V~ or 120V~, 50/60 Hz

ORDERING INFORMATION

Catalog No. Description

D1100-230V* AccuBlock Digital Dry Bath, single block capacity, 230V D1200-230V* AccuBlock Digital Dry Bath, dual block capacity, 230V

See page 23 for available block formats

*230V product includes both -EU and -UK power cords. For 120V units, remove -230V from end of catalog number.



Incubators - dry bath blocks



Dry Bath Blocks

Designed for use with the *AccuBlock* Digital Dry Baths on the previous page, these blocks are supplied in a variety of different formats to accept tubes from 0.2 mL to 50 mL as well as microplates and slides. A solid block is also available for custom machining.

The blocks are made of high grade, non-porous aluminum and precision machined for a close fit with sample containers - important for fast and efficient heat transfer. Anodizing adds corrosion resistance.

Most blocks, except those designed for use with plates and slides, include a position for a thermometer and a hole for use with the block lifter tool (supplied with the bath). The unique *PopStopper* accessory, sold separately, fits on the microtube blocks to keep tube lids from popping open during heating.

The new *AccuRack*™ accessory accommodates 20 x 1.5 mL tubes and fits onto the D1105A block. The rack can be used to quickly transfer sample into and out of the block and is self standing. Insulated handles protect users fingers. The rack can be used at temperatures up to 150°C and is autoclavable.

- **■** Corrosion resistant, anodized aluminum
- Blocks for tubes from 0.2 mL to 50 mL, plates and slides
- Precision machined for a close fit and efficient heat transfer
- Solid block available for custom machining



| AAda | D1105A-Rack |
|------|-------------|
| | |

| SPECIFICATIONS | |
|---|---|
| Construction Thermometer well Compatibility | Anodized, high grade, non-porous aluminum Available in all blocks except those used with plates and slides Labnet's high grade blocks will work in any manufacturers' dry bath with an opening of 3.05 x 3.60 inches. Block D1196-PCR requires a depth of 2.125 inches or less. |

| ORDERING INFORMATION | |
|----------------------|---|
| Catalog No. | Description |
| D1101 | Solid Block for machining (no holes) |
| D1102 | Block, 48 x 0.2 mL PCR tubes or 6 x 0.2 mL strips |
| D1102A | Block, 20 x 2.0 mL tubes |
| D1105 | Block, 24 x 0.5 mL tubes |
| D1105A | Block, 24 x 1.5 mL tubes |
| D1105A-RACK | AccuRack accessory for 20 x 1.5 mL tubes, compatible with D1105A, pack of 3 |
| D1106 | Block, 35 x 6 mm tubes |
| D1110 | Block, 20 x 10 mm tubes |
| D1112 | Block, 20 x 12 mm tubes |
| D1113 | Block, 20 x 13 mm tubes |
| D1115-TALL | Block, 12 x 15 mL centrifuge tubes |
| D1116 | Block, 12 x 15 or 16 mm tubes |
| D1117 | Block, 12 x 17 mm tubes |
| D1120 | Block, 6 x 20 mm tubes |
| D1125 | Block, 6 x 25 mm tubes |
| D1150-TALL | Block, 5 x 50 mL centrifuge tubes |
| D1196-PCR | Single Block, 96 well PCR plate, skirted or nonskirted (for single block unit only) |
| D1296 | Dual Block, 96 well microtiter plate or 4 slides (for dual block unit only) |
| D1296-PCR | Dual Block, 96 well PCR plate, skirted or nonskirted (for dual block unit only) |
| D1100-PS | PopStopper for microtube blocks, D1102, D1102A, D1105, D1105A |
| D12384 | Dual Block, 384 well PCR plate |

